

Don & Low Ltd Nonwovens

Glamis Road
Forfar
Angus DD8 1EY

Tel: 01307 452600 Fax: 01307 452610

e-mail: nonwovens@donlow.co.uk

website: www.donlow.co.uk



Agrément Certificate

89/2313

Product Sheet 1

DON & LOW CONSTRUCTION BREATHER MEMBRANES

DALTEX FRAMESHIELD 100

This Agrément Certificate Product Sheet⁽¹⁾ relates to Daltex Frameshield⁽²⁾ 100, for use as a breather membrane in timber-frame and steel-frame walls with a cavity and a masonry outer leaf, weatherboarding or tile/slate cladding.

(1) Hereinafter referred to as 'Certificate'.

(2) Daltex Frameshield is a registered trademark of Don & Low Ltd Nonwovens.

CERTIFICATION INCLUDES:

- factors relating to compliance with Building Regulations where applicable
- factors relating to additional non-regulatory information where applicable
- independently verified technical specification
- assessment criteria and technical investigations
- design considerations
- installation guidance
- regular surveillance of production
- formal three-yearly review.



KEY FACTORS ASSESSED

Weathertightness — the product will contribute to protecting a wall against water penetration (see section 6).

Risk of condensation — the product has a low resistance to water vapour transmission and can contribute to reducing the risk of interstitial condensation (see section 7).

Strength — the product has adequate strength to resist damage during the construction of walls (see section 8).

Properties in relation to fire — the product is classified as Class F in accordance with BS EN 13501-1 : 2007 and its use is restricted in some cases by the national Building Regulations (see section 9).

Durability — the product will have a life equal to that of the building in which it is installed (see section 11).



The BBA has awarded this Certificate to the company named above for the product described herein. This product has been assessed by the BBA as being fit for its intended use provided it is installed, used and maintained as set out in this Certificate.

On behalf of the British Board of Agrément

Date of Sixth issue: 14 December 2016

John Albon – Head of Approvals
Construction Products

Claire Curtis-Thomas
Chief Executive

Originally certificated on 14 November 1989

Certificate amended on 30 January 2019 to update section 6.2.

Certificate amended on 8 February 2019 to include Requirement B4(1) and associated text.

The BBA is a UKAS accredited certification body – Number 113.

*The schedule of the current scope of accreditation for product certification is available in pdf format via the UKAS link on the BBA website at www.bbacerts.co.uk
Readers are advised to check the validity and latest issue number of this Agrément Certificate by either referring to the BBA website or contacting the BBA direct.*

Any photographs are for illustrative purposes only, do not constitute advice and should not be relied upon.

British Board of Agrément

Bucknalls Lane
Watford
Herts WD25 9BA

©2016

tel: 01923 665300
clientservices@bbacerts.co.uk
www.bbacerts.co.uk

Regulations

In the opinion of the BBA, Daltex Frameshield 100, if installed, used and maintained in accordance with this Certificate, can satisfy or contribute to satisfying the relevant requirements of the following Building Regulations (the presence of a UK map indicates that the subject is related to the Building Regulations in the region or regions of the UK depicted):



The Building Regulations 2010 (England and Wales) (as amended)

Regulation:	B3(3)(4)	External fire spread
Comment:	The product can contribute to satisfying this Requirement. See section 9.1 of this Certificate.	
Regulation:	B4(1)	External fire spread
Comment:	The product is restricted by this Requirement. See section 9 of this Certificate.	
Requirement:	C2(b)	Resistance to moisture
Comment:	The product will contribute to a wall meeting this Requirement. See section 6.1 of this Certificate.	
Requirement:	C2(c)	Resistance to moisture
Comment:	The product can contribute to limiting the risk of condensation. See section 7.1 of this Certificate.	
Regulation:	7	Materials and workmanship (applicable to Wales only)
Regulation:	7(1)	Materials and workmanship (applicable to England only)
Comment:	The product is acceptable. See section 11 and the <i>Installation</i> part of this Certificate.	



The Building (Scotland) Regulations 2004 (as amended)

Regulation:	8(1)	Durability, workmanship and fitness of materials
Comment:	The product is acceptable. See section 11 and the <i>Installation</i> part of this Certificate.	
Regulation:	9	Building standards applicable to construction
Standard:	2.4	Cavities
Comment:	The product can contribute to satisfying this Standard with respect to clause 2.4.2 ⁽¹⁾⁽²⁾ . See section 9.1 of this Certificate.	
Standard:	3.10	Precipitation
Comment:	The product will contribute to a wall satisfying clauses 3.10.1 ⁽¹⁾⁽²⁾ and 3.10.5 ⁽¹⁾⁽²⁾ of this Standard. See section 6.1 of this Certificate.	
Standard:	3.15	Condensation
Comment:	The product can contribute to limiting the risk of condensation with reference to clauses 3.15.1 ⁽¹⁾ and 3.15.4 ⁽¹⁾ of this Standard. See section 7.1 of this Certificate.	
Standard:	7.1(a)	Statement of sustainability
Comment:	The product can contribute to meeting the relevant requirements of Regulation 9, Standards 1 to 6 and therefore will contribute to a construction meeting a bronze level of sustainability as defined in this Standard.	
Regulation:	12	Building standards applicable to conversions
Comment:	Comments in relation to the product under Regulation 9, Standards 1 to 6 also apply to this Regulation, with reference to clause 0.12.1 ⁽¹⁾⁽²⁾ and Schedule 6 ⁽¹⁾⁽²⁾ .	

(1) Technical Handbook (Domestic).

(2) Technical Handbook (Non-Domestic).



The Building Regulations (Northern Ireland) 2012 (as amended)

Regulation:	23(a)(i) (iii)(b)(i)	Fitness of materials and workmanship
Comment:	The product is acceptable. See section 11 and the <i>Installation</i> part of this Certificate.	
Regulation:	28(b)	Resistance to moisture and weather
Comment:	The product will contribute to a wall satisfying this Regulation. See section 6.1 of this Certificate.	
Regulation:	29	Condensation
Comment:	The product can contribute to limiting the risk of condensation. See section 7.1 of this Certificate.	
Regulation:	35(3)(4)	Internal fire spread - structure
Comment:	The product can contribute to satisfying this Regulation. See section 9.1 of this Certificate.	

Construction (Design and Management) Regulations 2015

Construction (Design and Management) Regulations (Northern Ireland) 2016

Information in this Certificate may assist the client, designer (including Principal Designer) and contractor (including Principal Contractor) to address their obligations under these Regulations.

See section: 1 *Description* of this Certificate.

Additional Information

NHBC Standards 2016

NHBC accepts the use of Daltex Frameshield 100, provided it is installed, used and maintained in accordance with this Certificate, in relation to *NHBC Standards*, Chapters 6.2 *External timber framed walls* and 6.10 *Light steel framed walls and floors*.

CE marking

The Certificate holder has taken the responsibility of CE marking the product in accordance with harmonised European Standard BS EN 13859-2 : 2014. An asterisk (*) appearing in this Certificate indicates that data shown are given in the manufacturer's Declaration of Performance.

Technical Specification

1 Description

Daltex Frameshield 100 is a spunbonded polypropylene material with the nominal characteristics given in Table 1.

Table 1 Nominal characteristics

Characteristic (unit)	Frameshield 100
Thickness (mm)	0.5
Mass per unit area* ($\text{g}\cdot\text{m}^{-2}$)	100
Roll length* (m)	100 ⁽¹⁾
Roll width* (m)	1.5 to 3.0 ⁽¹⁾
Colour upper lower	grey ⁽¹⁾ grey ⁽¹⁾
Tensile strength* ($\text{N}\cdot 50\text{ mm}^{-1}$) longitudinal transverse	240 180
Elongation* (%) longitudinal transverse	85 100
Tear resistance* (N) longitudinal transverse	135 145
Resistance to penetration of air ($\text{m}^3/\text{m}^2\cdot\text{h}\cdot 50\text{ Pa}^{-1}$)	320
Watertightness* unaged aged ⁽²⁾	W2 W2
Water vapour transmission* (S_d) (m)	0.006
Vapour resistance ($\text{MN}\cdot\text{s}\cdot\text{g}^{-1}$)	0.03

(1) Other roll sizes and colours are available.

(2) Aged in accordance with BS EN 13859-2 : 2014, Annex C.

2 Manufacture

2.1 The membrane is manufactured by extruding polypropylene to produce fibres. The fibres are spun and bonded together using a combination of heat and pressure in a continuous process.

2.2 As part of the assessment and ongoing surveillance of product quality, the BBA has:

- agreed with the manufacturer the quality control procedures and product testing to be undertaken
- assessed and agreed the quality control operated over batches of incoming materials
- monitored the production process and verified that it is in accordance with the documented process
- evaluated the process for management of nonconformities
- checked that equipment has been properly tested and calibrated
- undertaken to carry out the above measures on a regular basis through a surveillance process, to verify that the specifications and quality control being operated by the manufacturer are being maintained.

2.3 The management system of Don & Low Ltd Nonwovens has been assessed and registered as meeting the requirements of BS EN ISO 9001 : 2008 by BSI (Certificate FM 45536).

2.4 The product is marketed by the product's UK distributor, A Proctor Group, The Haugh, Blairgowrie, Perthshire, PH10 7ER, tel: 01250 872261, fax: 01250 872727, e-mail : contact@proctorgroup.com, website: www.proctorgroup.com

3 Delivery and site handling

3.1 The product is delivered to site in polythene wrappers bearing the manufacturer's name, the grade identification and the BBA logo including the number of this Certificate.

3.2 The rolls should be stored flat or on end on a smooth, clean, dry surface, under cover and protected from sunlight.

Assessment and Technical Investigations

The following is a summary of the assessment and technical investigations carried out on Daltex Frameshield 100.

4 Use

4.1 Daltex Frameshield 100 is satisfactory for use as on-site or factory-applied breather membranes in timber-frame and steel-frame walls with a cavity and a masonry outer leaf, weatherboarding or tile/slate cladding.

4.2 In the absence of other guidance, suitable timber-frame and steel-frame constructions are defined as those designed and built in accordance with *NHBC Standards 2016*, Chapters 6.2 and 6.10 respectively.

4.3 The product meets the requirements for a Class W2* material and meets the NHBC requirements given in *NHBC Standards 2016*, Chapter 6.2, as a high-performance breather membrane for use in very severe conditions⁽¹⁾.

(1) Very severe conditions are defined in the *NHBC Standards 2016*, Chapter 6.1, Clause 6.1.6 *Exposure* — see Figure 1 therein showing categories of exposure to wind-driven rain.

5 Practicability of installation

The product can be installed by a competent general builder, or a contractor, experienced with this type of product.

6 Weathertightness



6.1 The product is classified as Class W2* in accordance with BS EN 13859-2 : 2014. The product will resist liquid water penetration and wind-blown snow and will protect the sheathing and frame from external moisture.

6.2 The period of installation of the brickwork should be kept to a minimum. The membrane should not be used as a temporary waterproof covering during this time.

7 Risk of condensation



7.1 For design purposes, the product has a resistance to water vapour transmission of less than or equal to $0.6 \text{ MN} \cdot \text{s} \cdot \text{g}^{-1}$ and is classified as a breather membrane in accordance with BS 5250 : 2011, Annex G. Walls incorporating the product will therefore adequately limit the risk of interstitial condensation when designed and constructed in accordance with BS 5250 : 2011, Annex G.

7.2 The risk of condensation occurring within the wall of the timber- or steel-frame building will depend upon the properties and vapour resistance of the other materials used in the construction, the internal and external conditions and the effectiveness of the internal vapour control layer.

8 Strength

8.1 The product will resist the normal loads associated with construction and installation into timber- and steel-frame constructions.

8.2 The product is not adversely affected by water and will retain its properties when wet.

9 Properties in relation to fire



9.1 The product is classified* as Class F in accordance with BS EN 13501-1 : 2007. Where the product forms the face of a cavity the permissible areas of use and the spacing of cavity barriers are restricted by the national Building Regulations.



9.2 The product should not be used on buildings in England that have a storey at least 18 m above ground level and contain; one or more dwellings, an institution, a room for residential purposes (excluding any room in a hostel, hotel or boarding house), student accommodation, care homes, sheltered housing, hospitals or dormitories in boarding schools.

10 Maintenance

As the product is confined to the wall space and has suitable durability, maintenance is not required. However, any damage occurring before enclosure must be repaired (see section 15).

11 Durability



The product will be unaffected by the normal conditions found in a timber- or steel-frame wall and will have a life equal to that of the building in which it is installed.

12 Reuse and recyclability

The product is made of polyolefins, which can be recycled.

Installation

13 General

Daltex Frameshield 100 must be installed in accordance with the marketing company's instructions and the recommendations given in *NHBC Standards* 2016, Chapters 6.2 and 6.10, where appropriate.

14 Procedure

14.1 The product must be secured at regular intervals, not exceeding 500 mm, with austenitic stainless steel staples or nails to prevent damage by wind action (See Figures 1, 2 and 3).

Figure 1 Factory method of installation on timber- or steel-frame panel




Figure 2 Site installation – external corner






Figure 3 Site installation - opening



14.2 Upper layers should overlap lower layers to shed water away from the sheathing. Vertical laps should be staggered wherever possible (See Figure 4).

Figure 4 Membrane installation



14.3 Laps should not be more than 100 mm horizontally and 150 mm vertically.

14.4 It is essential that the lowest timbers are protected from moisture and that the positions of the studs are marked on the face of the breather membrane, preferably by tape, to enable fixing of wall ties or battens.

15 Repair

The product can be damaged by careless handling, high winds or vandalism, and should not remain uncovered for longer than necessary. Damage to the membrane must be repaired prior to the installation of external walls or claddings by laying another sheet over the damaged area and sealing it correctly, ensuring water is shed away from the sheathing.

16 Tests

An assessment was made of data to BS EN 13859-2 : 2014 in relation to:

- dimensions
- mass per unit area
- tensile strength and elongation
- resistance to tear
- dimensional stability
- resistance to water penetration
- resistance to artificial ageing
- resistance to penetration of air
- water vapour transmission.

17 Investigations

17.1 The manufacturing process was evaluated, including the methods adopted for quality control, and details were obtained of the quality and composition of the materials used.

17.2 Visits were made to sites in progress to assess the practicability of installation.

17.3 An examination was made of independent fire test data from a UKAS-approved testing laboratory.

Bibliography

BS 5250 : 2011 + A1 : 2016 *Code of practice for control of condensation in buildings*

BS EN 13501-1 : 2007 + A1 : 2009 *Fire classification of construction products and building elements — Classification using test data from reaction to fire tests*

BS EN 13859-2 : 2014 *Flexible sheets for waterproofing — Definitions and characteristics of underlays — Underlays for walls*

BS EN ISO 9001 : 2008 *Quality management systems — Requirements*

18 Conditions

18.1 This Certificate:

- relates only to the product/system that is named and described on the front page
- is issued only to the company, firm, organisation or person named on the front page – no other company, firm, organisation or person may hold claim that this Certificate has been issued to them
- is valid only within the UK
- has to be read, considered and used as a whole document – it may be misleading and will be incomplete to be selective
- is copyright of the BBA
- is subject to English Law.

18.2 Publications, documents, specifications, legislation, regulations, standards and the like referenced in this Certificate are those that were current and/or deemed relevant by the BBA at the date of issue or reissue of this Certificate.

18.3 This Certificate will remain valid for an unlimited period provided that the product/system and its manufacture and/or fabrication, including all related and relevant parts and processes thereof:

- are maintained at or above the levels which have been assessed and found to be satisfactory by the BBA
- continue to be checked as and when deemed appropriate by the BBA under arrangements that it will determine
- are reviewed by the BBA as and when it considers appropriate.

18.4 The BBA has used due skill, care and diligence in preparing this Certificate, but no warranty is provided.

18.5 In issuing this Certificate the BBA is not responsible and is excluded from any liability to any company, firm, organisation or person, for any matters arising directly or indirectly from:

- the presence or absence of any patent, intellectual property or similar rights subsisting in the product/system or any other product/system
- the right of the Certificate holder to manufacture, supply, install, maintain or market the product/system
- actual installations of the product/system, including their nature, design, methods, performance, workmanship and maintenance
- any works and constructions in which the product/system is installed, including their nature, design, methods, performance, workmanship and maintenance
- any loss or damage, including personal injury, howsoever caused by the product/system, including its manufacture, supply, installation, use, maintenance and removal
- any claims by the manufacturer relating to CE marking.

18.6 Any information relating to the manufacture, supply, installation, use, maintenance and removal of this product/system which is contained or referred to in this Certificate is the minimum required to be met when the product/system is manufactured, supplied, installed, used, maintained and removed. It does not purport in any way to restate the requirements of the Health and Safety at Work etc. Act 1974, or of any other statutory, common law or other duty which may exist at the date of issue or reissue of this Certificate; nor is conformity with such information to be taken as satisfying the requirements of the 1974 Act or of any statutory, common law or other duty of care.