

CLADSHIELD

Cladshield

Product specification to be Cladshield by The A Proctor Group, Blairgowrie

Manufacturer

Name A Proctor Group Ltd
 Web www.proctorgroup.com
 Email technical@proctorgroup.com
 Tel +44 (0) 1250 872261
 Fax +44 (0) 1250 872727
 Address The Haugh, Blairgowrie, Perthshire PH10 7ER

Detailed Description

Vapour Permeable Underlay to be used shall be Cladshield supplied by The A Proctor Group, Blairgowrie. Cladshield is a single layer spun-bonded polypropylene vapour and air permeable underlay designed for use in lightweight industrial roofing and wall systems.

Product

Product performance specification as follows:

Thickness

0.5mm

Roll Size

100m x 1.6m

Colour

Grey

Material

Polypropylene Spunbond

Certification

CE Mark

Technical Properties

- Mass per unit area: to be no less than 100g/m²
- Resistance to Water Penetration: to be no less than W2 when tested to EN 13111
- Vapour Resistance: to be no more than 0.006m when tested to EN ISO 12572
- Resistance to Tear: to be no less than MD 135N; CD 145N when tested to EN 12310-1
- Tensile Strength: to be no less than MD 240N; CD 180N when tested to EN 12311-1
- Cladshield is a high performance breather membrane designed primarily for use in lightweight industrial, roofing and wall systems. Cladshield controls the escape of water vapour from the roof and cladding structure whilst increased water resistance prevents the ingress of rain or moisture.
- Reaction to Fire: to be no less than Class E.

Benefits

- Ideal choice for high specification industrial roofing and cladding
- Made in the UK

Product Reference [Cladshield](#)

Revision Date: 11.03.19