

Proctorwrap® Reflect

PRODUCT: Proctorwrap Reflect
COMPOSITION: Flexible sheets for waterproofing - Underlays for walls EN 13859-2:2014
STANDARDS: EN 13859-2:2010
APPROVED BODY: Fire Lab zoo (2904) and Technicky a skusobny ustav stavebny (1301) performed an initial type test under system 3.

Physical Properties	Test Method	Mean results	Tolerances	
			Minimum	Maximum
Reaction to fire	EN 13859-2:2014	Class E	-	-
Resistance to water penetration		Class W2	-	-
Water vapour transmission		Sd 0.08m	0.02	0.10
Tensile force		MD 190 N/50mm CD 180 N/50mm	170 160	220 210
Elongation		MD 80% CD 90%	60% 70%	100% 110%
Tear resistance		MD 220 N CD 220 N	200N 200N	250N 250N
Resistance to penetration of air with 50 Pa pressure		≤ 20 m³/h*m²*50Pa	-	-

* Difference to non-aged product performance

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Manufactured By:

The A. Proctor Group Ltd.
 The Haugh
 Blairgowrie
 United Kingdom
 PH10 7ER

Telephone: +44(0)1250 872261
Fax: +44(0)1250 872727
Web: www.proctorgroup.com

Signed for and on behalf of The A. Proctor Group Ltd.

Name: 

Position: Technical Director

Place: The Haugh, Blairgowrie Date: 08/07/2025



Download a brochure from
 our website...

www.proctorgroup.com

contact@proctorgroup.com | +44 (0) 1250 872261

Revised: June 2025

Version: 1.001

Next review due: June 2026

